



**To ensure faultless operation
the compressed air supply must be
filtered and oiled.**

Pneumatic chain hoist model CPA with suspension hook or with integrated trolley

Capacity 2000 - 10000 kg

The conception is in accordance with the design of the model CPE.

With 100 % duty rating and an unlimited number of starts the model CPA is suitable for heavy duty applications. It is insusceptible to contamination, humidity and aggressive mediums from the outside. The hoists are composed of three main components which makes service easy and inexpensive.

Features

- Designed for operating pressures of 4 to 6 bar.
 - Robust rotating piston motor has an adjustable spring pressure brake that holds the load secure even in the event of an air failure.
 - The standard, oil bath lubricated planetary gearbox is particularly smooth running and enables a low overall height.
 - High starting torque due to switching valves in the motor body.
 - Low noise emission due to large dimension silencer.
 - Sensitive control by means of 2 resp. 4 button pendant control with emergency-stop.
 - Up to 3000 kg only one chain fall, leading to a low overall height.
 - The 5-pocket load chain sheave, manufactured from wear resistant case hardening steel, is matched perfectly to the load chain to guarantee smooth and precise chain motion.
 - Drop forged suspension and load hooks are made from non-aging, high tensile steel and fitted with robust safety latches.
 - The standard case hardened and zinc-plated link chain is matched perfectly to the load chain to guarantee smooth and precise chain motion.
- All requirements of national and international standards and regulations are fulfilled.

Options

- Manual and pneumatic trolleys.
- Rope control
- Stainless steel load chain.