

Grade 8 Two Leg Chain Slings EN 818-4

| Chain Size mm | Straight Lift 0°-45° | Straight Lift 45°-60° | Choke Hitch 0°-45° | Choke Hitch 45°-60° | Double Basket 0°-45° | Double Basket 45°-60° |
|------------------|-------------------------|--------------------------|-----------------------|------------------------|-------------------------|--------------------------|
| 7mm | 2.1 | 1.5 | 1.6 | 1.2 | 2.1 | 1.5 |
| 8mm | 2.8 | 2.0 | 2.2 | 1.6 | 2.8 | 2.0 |
| 10mm | 4.25 | 3.15 | 3.4 | 2.5 | 4.25 | 3.15 |
| 13mm | 7.5 | 5.3 | 6.0 | 4.2 | 7.5 | 5.3 |
| 16mm | 11.2 | 8.0 | 9.0 | 6.4 | 11.2 | 8.0 |
| 20mm | 17.0 | 12.5 | 13.6 | 10.0 | 17.0 | 12.5 |
| 22mm | 21.2 | 15.0 | 17.0 | 12.0 | 21.2 | 15.0 |
| 26mm | 30.0 | 21.2 | 24.0 | 17.0 | 30.0 | 21.2 |
| 32mm | 45.0 | 31.5 | 36.0 | 25.2 | 45.0 | 31.5 |

All loads shown in tonnes

