

Retractable fall arrest block model HSG-G-6 and model HSG-S

Conform to EN 360

- Plastic housing
- Fall indicator
- Galvanized steel wire rope (model HSG-S) and webbing (model HSG-G 6).
- Rope length 6 up to 28 m (model HSG-S) webbing length 6 m (model HSG-G 6).
- End connection:
swivel twist lock carabiner AXK 10 SI, 23 mm opening.

Technical data model HSG-G 6 and model HSG-S

Model	EAN-No. 4025092*	Length m
HSG-G-6	*470728	6.0
HSG-S 6	*165006	6.0
HSG-S-10	*165013	10.0
HSG-S-15	*165020	15.0
HSG-S-20	*165037	20.0
HSG-S-25	*165044	25.0
HSG-S-28	*165068	28.0



Retractable fall arrest block model HSG-G and model HSG-G-ACB

Conform to EN 360

- Plastic housing (model HSG-G), aluminium housing (model HSG-G-ACB).
- Fall indicator (model HSG-G)
- Abrasion resistant 45 mm webbing (model HSG-G) or 30 mm webbing (model HSG-G-ACB) with coming out forces under 3 kN.
- End connections:
1 x screw gate snap hook, 18 mm opening,
1 x carabiner AXK 10 S, 22 mm opening.

Technical data model HSG-G and model HSG-G-ACB

Model	EAN-No. 4025092*	Description	Length m
HSG-G	*165075	with carabiner	2.25
HSG-G-ACB	*289832	special system for powered access platforms (IPAF)	1.8

